

Window World[®]

8000 SERIES IMPACT-RESISTANT CASEMENT WINDOWS

8000 Series
Impact-Resistant
Casement Windows
in White



AMERICA'S EXTERIOR REMODELERSM

Improving Homes. Changing Lives.[®]

Interior & Exterior Vinyl Colors



White Tan Clay Black *

*Black interior available in laminate only.

Exterior Laminate Colors



Bronze Brown Black Earthtone



Hunter Green Silver

Tinted Glass



Tinted Grey Tinted Bronze Obscure

Privacy Glass



Tinted Grey Tinted Bronze Obscure

Folding Handles



White Tan Clay
Bright Brass Satin Nickel Antique Brass Bronze

Features:

- Fully concealed multi-point lock.
- Nesting folding handle.
- Sturdy vinyl frames.
- Heavy-gauge steel hinges.
- Opens to almost 90 degrees.
- Optional stainless steel hinge.
- Double-strength, impact-resistant laminated glass.



No Fade Vinyl Colors

8000 Series windows are available in three colors to blend with virtually any home color palette. The color is extruded through the vinyl material so it will not fade or discolor over time.

Exterior Laminate Colors


Expanding your design options, 8000 Series windows are also available in six additional exterior colors. Please see limitations listed below, or contact your Window World design consultant for more detail.

Hardware

Hardware is color matched to your window as a standard feature. Optional plated hardware is also available in four finishes - Satin Nickel, Bright Brass, Antique Brass, and Bronze.

Grid Options

Optional contoured grids are located inside the glass unit to provide a smooth cleaning surface. Available in two patterns.



Colonial Perimeter

IMPACT-RESISTANT CASEMENT WINDOW THERMAL PERFORMANCE													
MAX TEST SIZE	GLASS STRENGTH	AIR INFILTR. RESISTANCE	WATER TEST PRESSURE	DESIGN PRESSURE	OVERALL PERF. RATING	LE (LOW-E) / CL (CLEAR)				LE (LOW-E) / EP (LOW-E)			
						U-FACTOR	R-VALUE	SHGC	VT	U-FACTOR	R-VALUE	SHGC	VT
CASEMENT													
36" x 72" *	LAMI (SGP) / DST	<0.01 cfm/ft2	15.00 psf	+65 / -70 psf	LC-PG65	0.26	3.85	0.18	0.39	0.23	4.37	0.17	0.35
36" x 72" *	LAMI (PVB) / DST	<0.01 cfm/ft2	15.00 psf	+55 / -55 psf	LC-PG55	0.26	3.85	0.18	0.4	0.23	4.37	0.17	0.36
36" x 72"	LAMI (PVB) / DS	<0.01 cfm/ft2	7.50 psf	+50 / -50 psf	LC-PG50	0.26	3.85	0.18	0.4	0.23	4.37	0.17	0.36
AWNING													
53" x 32" *	LAMI (PVB) / DST	<0.01 cfm/ft2	15.00 psf	+55 / -55 psf	LC-PG55	0.26	3.82	0.18	0.4	0.24	4.22	0.17	0.36
53" x 32"	LAMI (PVB) / DS	<0.01 cfm/ft2	9.75 psf	+50 / -50 psf	LC-PG50	0.26	3.82	0.18	0.4	0.24	4.22	0.17	0.36
54" x 67"	DS / LAMI (P9)	<0.01 cfm/ft2	15.00 psf	+50 / -50 psf	LC-PG50	0.26	3.90	0.22	0.50	0.22	4.58	0.22	0.50

*Approved for use in HVHZ.

All Impact Testing performed in accordance with ASTM E 1886 & ASTM E 1996 (Wind Zone 4 - Missile Level D).

All Testing performed for products approved for use in HVHZ was done so in accordance with TAS 201, 202, 203.

All thermal performance values listed reflect the use of NO GRIDS.



*Restrictions may apply. For complete details, see the warranty at your nearest Window World store.

©2024 Window World International, LLC. (International). Window World®, the Window World logo, the Window World Circle "W", and SolarZone® are registered trademarks. "Improving Homes. Changing Lives.™" is a registered service mark, and AMERICA'S EXTERIOR REMODELERSM is a service mark of International. Usage of all the referenced marks is limited to authorized licensees of International or franchisees of Window World, Inc., International's authorized licensee. This Window World® franchise location is independently owned and operated under license from Window World, Inc. Specifications subject to change without notice. Colors are reproduced by lithographic process and may vary slightly from colors of actual product. Printed in USA. WC-WWI-512 07/24 2K/SO